



DP100



- Prints 55 full-color envelopes per minute
- A top-load bottom-feed feeder and a coordinated high-capacity conveyor insures continuous production
- Capable of feeding a wide variety of products and sizes such as envelopes, card stock, postcards, labels, standard paper, and more.
- Feeds sizes from 3" x 5" up to 12" x 18"
- Prints return address, logo, mailing address, bar code, and personalized messages all in one pass.
- Feeding letterhead stock from the standard paper drawers allows for an exact color-match between letterhead, business cards, and printed envelopes.

See it on the web at: <http://www.intoprinttech.com>

Intoprint Technologies

5119 Hollins Road • Roanoke, VA 24019 • (540) 362-1226 • Toll Free 1-800-833-4493



DP100

TECHNICAL SPECIFICATIONS

Printer

- **Print Speed:** Up to 36 ppm Color; up to 40 ppm Monochrome (Letter-size); Up to 55 ppm Color/Monochrome (#10 Envelopes)
- **Processor:** 800 MHz PowerPC 750
- **File Storage:** 40 GB Hard Disk Drive
- **Print Resolution:** Up to 1200 x 600 dpi resolution with High Definition Color technology
- **Print Technology:** CMYK LED Technology
- **Duty Cycle:** Up to 150,000 pages per month
- **Connectivity:** 10/100/1000 Ethernet; High-Speed USB v2.0, Parallel

Compatibility

- **Emulations:** PCL® 5c, PCL 6; Adobe® PostScript 3 standard
- **Operating Systems:** Stand-alone and network - Windows Vista® (32/64-bit), XP Home/Professional, 2003 Server (32/64-bit), 2000; Mac® OS 9.2/OS 10.2.4 and higher
- **Network and Protocols:** 10/100/1000 Base TX Ethernet card with internal Web server for printer and network card setup and management; includes POP3/APOP and SMTP Mail client for submission of print jobs and for alerts. All major network protocols supported - TCP/IP, Netware and Ethertalk. TCP/IP includes ARP, IP, ICMP, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMP, DNS, SSL/TLS, JetDirect protocols; Netware includes 3.x, 4.x, 5.x and 6 with full NDS and NDPS support - PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway
- **Typefaces:** Printer fonts - 86 scalable PCL fonts, 1 bitmap font, 10 TrueType® fonts, 136 Adobe PostScript Type 1 fonts, OCR A/B, USPS Barcode

System Memory

- **Standard/Maximum Imaging RAM:** 512 MB/1,024 MB
- **Flash Memory:** 4MB standard

Environmental

- **HxWxD without Feeder:** 54.88" x 26.48" x 34.59"
- **HxWxD with Feeder:** 108" x 26.48" x 34.59"
- **Power Consumption:** Typical 780W, Peak < 1500W, Idle 200W (average), Power Save Mode: 33W
- **ENERGY STAR® Compliance:** Yes

Color Controls

- **Ink Simulations:** SWOP®, Euroscale and others
- **Color Matching Modes:** sRGB, Monitor simulations
- **Color Management:** Color Matching software and Color Correct from OKI Printing Solutions, PS Gamma Adjuster, PostScript® CRD, Windows® ICM, Resident ICC Input/ Output Profiles (also create, download to printer, and manage new profiles). Supports color management systems that utilize ICC profiles (Apple®, ColorSync®, Microsoft® ICM, Adobe® applications, QuarkXPress™, CorelDRAW®)

Paper Handling - Trays

- **Paper Sizes:** Min 3" x 5"; Max 12" x 18"
- **Printer Paper Input:** 1,060 sheets standard (2 x 530-sheet tray)
- **Paper Weight:** Trays 1 thru 2 - 17 lb. bond-80 lb. cover (64-216 gsm); duplex - 20 lb. bond-65 lb. cover (75-188 gsm) for letter and tabloid sheets
- **Automatic Duplexer:** 2-sided printing standard
- **Paper Output:** Face-down stacker 500 sheet capacity

Feeder/Conveyor

- **Paper Input Capacity:** Up to 1,000 sheets/envelopes
- **Envelope Sizes:** Min 3" x 5"; Max 10" x 13"
- **Paper Sizes:** Min 3" x 5"; Max 12.9" x 19"
- **Paper Weight:** 17 lb. bond-170 lb. index (64-307 gsm)
- **Paper Output Capacity:** Up to 1000 envelopes

Consumables

- Refer to proposal for details



Intoprint Technologies

5119 Hollins Road • Roanoke, VA 24019 • (540) 362-1226 • Toll Free 1-800-833-4493